

# Shortest Paths

- **Input:** weighted, directed graph  $G = (V, E)$ , with weight function  $w : E \rightarrow \mathbf{R}$ .
- The **weight** of path  $p = \langle v_0, v_1, \dots, v_k \rangle$  is the sum of the weights of its constituent edges:


$$w(p) = \sum_{i=1}^k w(v_{i-1}, v_i) .$$

- The **shortest-path weight** from  $u$  to  $v$  is


$$\delta(u, v) = \begin{cases} \min\{w(p)\} & \text{if there is a path } p \text{ from } u \text{ to } v , \\ \infty & \text{otherwise .} \end{cases}$$

- A **shortest path** from vertex  $u$  to vertex  $v$  is then defined as any path  $p$  with weight  $w(p) = \delta(u, v)$ .

# Example



# Solution



# Shortest Paths

## Shortest Path Variants

- Single Source-Single Sink
- Single Source (all destinations from a source  $s$ )
- All Pairs

## Defs:

- Let  $\delta(v)$  be the real shortest path distance from  $s$  to  $v$
- Let  $d(v)$  be a value computed by an algorithm

## Edge Weights

- All non-negative
- Arbitrary

**Note:** Must have no negative cost cycles

# Single Source Shortest Paths

**Key Property: Subpaths of shortest paths are shortest paths** Given a weighted, directed graph  $G = (V, E)$  with weight function  $w : E \rightarrow \mathbb{R}$ , let  $p = \langle v_1, v_2, \dots, v_k \rangle$  be a shortest path from vertex  $v_1$  to vertex  $v_k$  and, for any  $i$  and  $j$  such that  $1 \leq i \leq j \leq k$ , let  $p_{ij} = \langle v_i, v_{i+1}, \dots, v_j \rangle$  be the subpath of  $p$  from vertex  $v_i$  to vertex  $v_j$ . Then,  $p_{ij}$  is a shortest path from  $v_i$  to  $v_j$ .

**Note: this is optimal substructure**

**Corollary 1** For all edges  $(u, v) \in E$ ,

$$\delta(v) \leq \delta(u) + w(u, v)$$

**Corollary 2** Shortest paths follow a tree of edges for which

$$\delta(v) = \delta(u) + w(u, v)$$

More precisely, any edge in a shortest path must satisfy

$$\delta(v) = \delta(u) + w(u, v)$$

# Relaxation


**Relax**( $u, v, w$ )

- 1 **if**  $d[v] > d[u] + w(u, v)$
- 2     **then**  $d[v] \leftarrow d[u] + w(u, v)$
- 3              $\pi[v] \leftarrow u$  (**keep track of actual path**)

**Lemma:** Assume that we initialize all  $d(v)$  to  $\infty$ ,  $d(s) = 0$  and execute a series of Relax operations. Then for all  $v$ ,  $d(v) \geq \delta(v)$ .

**Lemma:** Let  $P = e_1, \dots, e_k$  be a shortest path from  $s$  to  $v$ . After initialization, suppose that we relax the edges of  $P$  in order (but not necessarily consecutively). Then  $d(v) = \delta(v)$ .

# Example



# Algorithms

**Goal of an algorithm:** Relax the edges in a shortest path in order (but not necessarily consecutively).



# Algorithms

**Goal of an algorithm:** Relax the edges in a shortest path in order (but not necessarily consecutively).


**Bellman-Ford**( $G, w, s$ )

```
1  INITIALIZE-SINGLE-SOURCE( $G, s$ )
2  for  $i \leftarrow 1$  to  $|V[G]| - 1$ 
3      do for each edge  $(u, v) \in E[G]$ 
4          do RELAX( $u, v, w$ )
5  for each edge  $(u, v) \in E[G]$ 
6      do if  $d[v] > d[u] + w(u, v)$ 
7          then return FALSE
8  return TRUE
```

*Initialize – Single – Source*( $G, s$ )

```
1  for each vertex  $v \in V[G]$ 
2      do  $d[v] \leftarrow \infty$ 
3      do  $\pi[v] \leftarrow \text{NIL}$ 
4   $d[s] \leftarrow 0$ 
```

# Example



# Correctness of Bellman Ford

- Every shortest path must be relaxed in order
- If there are negative weight cycles, the algorithm will return false

**Running Time**  $O(VE)$


## All edges non-negative

- Dijkstra's algorithm, a greedy algorithm
- Similar in spirit to Prim's algorithm
- Idea: Run a discrete event simulation of breadth-first-search. Figure out how to implement it efficiently
- Can relax edges out of each vertex exactly once.

*Dijkstra*( $G, w, s$ )

```
1 INITIALIZE-SINGLE-SOURCE( $G, s$ )
2  $S \leftarrow \emptyset$ 
3  $Q \leftarrow V[G] \triangleright$  This line does  $V$  INSERTS
4 while  $Q \neq \emptyset$ 
5     do  $u \leftarrow$  EXTRACT-MIN( $Q$ )
6          $S \leftarrow S \cup \{u\}$ 
7         for each vertex  $v \in Adj[u]$ 
8             do RELAX( $u, v, w$ )  $\triangleright$  This line does a DECREASE-KEY
```

# Example



## Correctness

**Correctness of Dijkstra's algorithm** Dijkstra's algorithm, run on a weighted, directed graph  $G = (V, E)$  with nonnegative weight function  $w$  and source  $s$ , terminates with  $d[v] = \delta(s, v)$  for all vertices  $u \in V$ .

**Claim to Prove:** When  $v$  is put in  $S$ ,  $d(v) = \delta(v)$ .

# Proof

**Claim to Prove:** When  $v$  is put in  $S$ ,  $d(v) = \delta(v)$ .

## Proof

- $d(v) \geq \delta(v)$  because any algorithm that does a sequence of Relax calls has this property.
- Assume fpor that  $d(v) > \delta(v)$ , and that  $v$  is the first such vertex that is permanently labelled that has this property.
- Consider the state of the world just before  $v$  is put in  $S$ 
  - shortest path from  $s$  to  $v$  goes through an edge  $(x, y)$  where  $x \in S$  and  $y \notin S$  (it is possible that  $y = v$  and/or  $x = s$ ).
  - $d(x) = \delta(x)$ , because  $x \in S$
  - $d(y) = \delta(y)$  because  $(x, y)$  was relaxed when  $x$  was put in  $S$ .
- Putting these together with  $\delta(y) \leq \delta(v)$  because  $y$  is before  $v$  on a shortest path, we have

$$d(y) = \delta(y) \leq \delta(v) < d(v)$$

.

- $d(y) < d(v)$ , so the algorithm would have chosen to permanently label  $y$  and not  $v$ , which is a contradiction.

# Running Time

- $E$  decrease keys and  $V$  delete-min's
- $O(E \log V)$  using a heap
- $O(E + V \log V)$  using a Fibonacci heap




# Shortest Path in a DAG

Dag-Shortest-Paths( $G, w, s$ )

- 1 topologically sort the vertices of  $G$
- 2 INITIALIZE-SINGLE-SOURCE'( $G, s$ )
- 3 for each  $u$  taken in topological order
- 4     do for each  $v \in Adj[u]$
- 5         do RELAX( $u, v, w$ )

# Example



# Correctness and Running Time

**Correctness** If a weighted, directed graph  $G = (V, E)$  has source vertex  $s$  and no cycles, then at the termination of the DAG-SHORTEST-PATHS procedure,  $d[v] = \delta(s, v)$  for all vertices  $v \in V$ , and the predecessor subgraph  $G_\pi$  is a shortest-paths tree.

## Running Time

- Topological sort is linear time
- Each edge is relaxed once
- No additional data structure overhead

$O(V + E)$  time.