Simple Dispatch Rules

- We will first look at some simple dispatch rules: algorithms for which the decision about which job to run next is made based on the jobs and the time (but not on the history of jobs running, or by computing tentative schedules).
- These are also called greedy algorithms.

Goals:

- To recognize when simple dispatch rules apply.
- To prove that they are the correct algorithm.
- To analyze the running time of the algorithm.

$1||\Sigma C_j|$

Example:

	_
j	p_j
1	5
2	3
3	10
4	8
5	4

- What is the right algorithm?
- What is its running time?
- How do we prove it?

$$1|| \Sigma C_j$$

Example:

$$egin{array}{c|cccc} j & p_j \ \hline 1 & 5 \ 2 & 3 \ 3 & 10 \ 4 & 8 \ 5 & 4 \ \hline \end{array}$$

- What is the right algorithm? SPT
- What is its running time?
- How do we prove it?

$$1|| \Sigma C_j$$

Example:

$$egin{array}{c|cccc} j & p_j & & & \\ \hline 1 & 5 & & & \\ 2 & 3 & & & \\ 3 & 10 & & & \\ 4 & 8 & & & \\ 5 & 4 & & & \\ \end{array}$$

- What is the right algorithm?— SPT
- What is its running time? $O(n \log n)$
- How do we prove it?

$$1||\Sigma C_j|$$

Example:

$$egin{array}{c|cccc} j & p_j & & & \\ \hline 1 & 5 & & & \\ 2 & 3 & & & \\ 3 & 10 & & & \\ 4 & 8 & & & \\ 5 & 4 & & & \\ \hline \end{array}$$

- What is the right algorithm?— SPT
- What is its running time? $-O(n \log n)$
- How do we prove it? Interchange Argument

Basic format of an interchange argument

- Specify the simple dispatch rule X.
- \bullet Assume, for the purposed of contradiction, that you have an optimal schedule that does not obey the rule X.
- Find two specific jobs j and k that violate rule X.
- Show that if you interchange jobs j and k, then
 - The resulting schedule is still feasible.
 - The objective function value does not increase (for a minimization problem).
- You can then conclude that, via repeated swaps, there must exist an optimal schedule that satisfied rule X.

Comment: Even though the proof is boilerplate, you must provide enough mathematical detail that shows that your proof applies to the particular problem and the particular rule!

$1||\Sigma w_j C_j|$

- How can we figure out a simple dispatch rule?
- How do we prove it is correct Exchange Argument

$1||\Sigma w_j C_j|$

Example:

	. –			
j	p_j	w_{j}		
1	1	1		
2	3	2		
3	7	1		
4	10	20		

Questions:

- How can we figure out a simple dispatch rule?
- How do we prove it is correct Exchange Argument

Two answers to first question;

- Experiment with small examples and develop a plausible rule.
- Start an exchange argument and see what you need to make it work.

WSPT, Smith's rule

- Want to have large weight, small processing time jobs early
- ullet Schedule jobs in decreasing order of w_j/p_j .

Problems with Deadlines

Deadlines

- Can be hard (deadlines) or soft (due dates).
- Model Real Time scheduling.

Example 1

-					
j	p_j	d_{j}			
1	2	25			
2	4	13			
3	6	6			
4	7	19			
5	10	29			

Example 2

j	p_j	d_{j}
1	1	5
2	3	6
3	6	7
4	4	15

EDD - Earliest Due date

a.k.a. EDF - Earliest deadline first.

Theorem If, for an instance, on one machine with processing times and deadlines, there is a schedule meeting all deadlines, then EDF meets all deadlines.

What if you can't meet all deadlines:

- One metric: lateness $L_j = C_j d_j$
- \bullet 1|| L_{\max}
- Interpretation: if L_{max} is 4, then there is a schedule in which no job misses its deadline by more than 4 time units.

Question: Does EDD minimize L_{max} ?

Answer:

What if you can't meet all deadlines:

- One metric: lateness $L_j = C_j d_j$
- $\bullet 1 || L_{\max}$
- Interpretation: if L_{max} is 4, then there is a schedule in which no job misses its deadline by more than 4 time units.

Question: Does EDD minimize L_{max} ?

Answer: YES

- Reason 1. Think about $L_{\text{max}} = t$ as extending all deadlines by t.
- Reason 2. Interchange argument.

Adding Release Dates. $1|r_j|L_{\text{max}}$

Question: Does EDD still produce an optimal schedule?

j	$ r_j $	p_{j}	d_{j}
1	4	1	5
2	0	4	6

Maybe some other dispatch rule still works?

Adding release dates to a completion time problem.

$$1|r_j|\sum C_j$$

$$egin{array}{c|ccccc} {\bf Example 1} & egin{array}{c|cccc} j & r_j & p_j \\ \hline {f 1} & {f 0} & {f 100} \\ {f 2} & {f 40} & {f 1} \end{array}$$